



Features

- Zero Forward/Reverse Recovery Current
- High Blocking Voltage
- High Frequency Operation
- Positive Temperature Coefficient on V_F
- Temperature Independent Switching Behavior
- High surge current capability

$V_R = 1200\text{ V}$
 $I_F = 40\text{ A (}T_C=150^\circ\text{C)}^{**}$
 $Q_C = 186\text{ nC (}V_R=800\text{ V)}^{**}$


Benefits

- Higher System Efficiency
- Parallel Device Convenience without thermal runaway
- High Temperature Application
- No Switching loss
- Hard Switching & Higher Reliability
- Environmental Protection

Applications

- Servo Drives
- Solar / Wind Inverters
- AC/DC converters
- DC/DC converters
- Uninterruptable power supplies

TO-247-3



Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Value	Unit
Peak Repetitive Reverse Voltage	V_{RRM}		1200	V
Peak Reverse Surge Voltage	V_{RSM}		1200	V
DC Blocking Voltage	V_R		1200	V
Continuous Forward Current (per leg / per device)	I_F	$T_C=25^\circ\text{C}$ $T_C=135^\circ\text{C}$ $T_C=150^\circ\text{C}$	55/110 25/50 20/40	A
Non repetitive Forward Surge Current *	I_{FSM}	$T_C = 25^\circ\text{C}$, $t_p=10\text{ ms}$, Half Sine Pulse $T_C = 110^\circ\text{C}$, $t_p=10\text{ ms}$, Half Sine Pulse	140 130	A
Repetitive peak Forward Surge Current *	I_{FRM}	$T_C = 25^\circ\text{C}$, $t_p=10\text{ ms}$, Freq = 0.1Hz, 100 cycles, Half Sine Pulse $T_C = 110^\circ\text{C}$, $t_p=10\text{ ms}$, Freq = 0.1Hz, 100 cycles, Half Sine Pulse	110 100	A
Total power dissipation (per leg / per device)	P_D	$T_C=25^\circ\text{C}$ $T_C=110^\circ\text{C}$	250/430 108/180	W
Diode dv/dt ruggedness	dv/dt	$V_R = 0\text{-}1200\text{V}$	80	V/ns
Operating Junction Temperature	T_J		-55 to 175	$^\circ\text{C}$
Storage Temperature	T_{STG}		-55 to 175	$^\circ\text{C}$

Note : * Per leg ** Per device



Electrical Characteristics

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
DC Blocking Voltage *	V_{DC}	$T_J = 25^{\circ}C$	1200			V
Forward Voltage *	V_F	$I_F = 20A, T_J = 25^{\circ}C$		1.45	1.8	V
		$I_F = 20A, T_J = 125^{\circ}C$		1.8		V
		$I_F = 20A, T_J = 175^{\circ}C$		2.0		V
Reverse Current *	I_R	$V_R = 1200V, T_J = 25^{\circ}C$		10	200	μA
		$V_R = 1200V, T_J = 125^{\circ}C$		20	250	μA
		$V_R = 1200V, T_J = 175^{\circ}C$		50	300	μA
Total Capacitive Charge *	Q_C	$V_R = 800V, I_F = 20A,$ $di/dt = 200A/\mu s, T_J = 25^{\circ}C$		93		nC
Total Capacitance *	C	$V_R = 1V, T_J = 25^{\circ}C,$ Freq = 1MHz		1120		pF
		$V_R = 400V, T_J = 25^{\circ}C,$ Freq = 1MHz		92		
		$V_R = 800V, T_J = 25^{\circ}C,$ Freq = 1MHz		62		

Note: This is a majority carrier diode, so there is no reverse recovery charge

Thermal Characteristics

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Thermal Resistance ** (per device)	$R_{th(j-c)}$	junction-case		0.35		$^{\circ}C/W$

Note : * Per leg ** Per device



Typical Electrical Curves (Per Leg)




Figure 1. Forward Characteristics




Figure 2. Forward Characteristics




Figure 3. Reverse Characteristics




Figure 4. Power Derating




Figure 5. Capacitance vs Reverse Voltage





Figure 6. Recovery Charge vs Reverse Voltage



Package Dimensions

(TO-247-3 Package)



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	4.850	5.150	0.191	0.200
A1	2.200	2.600	0.087	0.102
b	1.000	1.400	0.039	0.055
b1	2.800	3.200	0.110	0.126
b2	1.800	2.200	0.071	0.087
c	0.500	0.700	0.020	0.028
c1	1.900	2.100	0.075	0.083
D	15.450	15.750	0.608	0.620
E1	3.500 REF		0.138 REF	
E2	3.600 REF		0.142 REF	
L	40.900	41.300	1.610	1.626
L1	24.800	25.100	0.976	0.988
L2	20.300	20.600	0.799	0.811
Φ	7.100	7.300	0.280	0.287
e	5.450 TYP		0.215 TYP	
H	5.980 REF		0.235 REF	
h	0.000	0.300	0.000	0.012

Package	Packing	Box Size L×W×H(mm)	Quantity(pcs/box)	Carton Size L×W×H(mm)	Quantity(pcs/carton)
TO-247	30pcs/Tube	570×155×50	450	580×340×125	1800