





FEATURES

- Low leakage current applications.
- Medium speed switching times.
- Surface mount package ideally suited for automatic Insertion.


SOT-23

APPLICATIONS

- High speed switching application.

ORDERING INFORMATION

Type No.	Marking	Package Code
BAS116	JV	SOT-23

MAXIMUM RATING @ Ta=25°C unless otherwise specified





Characteristic	Symbol	Limits	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	85	V
Working Peak Reverse Voltage	V_{RWM}		
DC Reverse Voltage	V_R		
RMS Reverse Voltage	$V_{R(RMS)}$	60	V
Forward Continuous Current	I_{FM}	215	mA
Repetitive Peak Forward Current	I_{FRM}	500	mA
Non-Repetitive Peak Forward Surge Current	I_{FSM}	4.0	A
@t=1.0μs		1.0	
@t=1.0ms		0.5	
Power Dissipation	P_d	250	mW
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$	500	°C/W
Operating Junction Temperature Range	T_j	150	°C
Storage Temperature Range	T_{STG}	-65 to +150	°C



ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified


Characteristic	Symbol	Min	Typ	MAX	UNIT	Test Condition
Reverse Breakdown Voltage	$V_{(BR)R}$	85	-	-	V	$I_R=100\mu A$
Forward Voltage	V_{FM}	-	-	0.9 1.0 1.1 1.25	V	$I_F=1mA$ $I_F=10mA$ $I_F=50mA$ $I_F=150mA$
Reverse Leakage Current	I_R	-	-	5.0 80	nA	$V_R=75V$ $V_R=75V, T_j=150^\circ C$
Junction Capacitance	C_j	-	2	-	pF	$V_R=0V, f=1.0MHz$
Reverse Recovery Time	t_{rr}	-	-	3	us	$I_F=I_R=10mA, t_{rr}=0.1*I_R$

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




PACKAGE OUTLINE

Plastic surface mounted package



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	0.90	1.10
D	0.30	0.50
E	0.35	0.48
G	1.80	2.00
H	0.02	0.10
J	0.05	0.15
K	2.20	2.60
All Dimensions in mm		

SOLDERING FOOTPRINT



Unit : mm

PACKAGE INFORMATION

Device	Package	Shipping
BAS116	SOT-23	3000 pcs / Tape & Reel