




FEATURES

- Fast switching speed
- For general purpose switching application
- High conductance
- One BAV70 circuit and one BAW56 circuit in one package
- Easily connected as full wave bridge



SOT-363

APPLICATIONS

- For general purpose switching application

ORDERING INFORMATION

Type No.	Marking	Package Code
BAV756DW	KCA	SOT-363





MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Characteristic	Value	Unit
V_{RM}	Non-Repetitive Peak Reverse Voltage	100	V
V_R	Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Reverse Voltage	75	V
$V_{R(RMS)}$	RMS Reverse Voltage	53	V
I_O	Average Rectified Output Current	150	mA
I_{FSM}	Non-Repetitive Peak Forward Surge Current	@t=1.0us 2.0 @t=1.0s 1.0	A
P_D	Power Dissipation	200	mW
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	625	°C/W
T_j, T_{stg}	Junction and Storage Temperature	-65 to +150	°C

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified


Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R=2.5\mu A$	75		V
Reverse voltage leakage current	I_R	$V_R=75V$ $V_R=75V, T_j=150^\circ C$ $V_R=25V, T_j=150^\circ C$ $V_R=20V$		2.5 50 30 25	μA μA μA nA
Forward voltage	V_F	$I_F=1.0mA$ $I_F=10mA$ $I_F=50mA$ $I_F=150mA$		0.715 0.855 1.0 1.25	V
Total Capacitance	C_T	$V_R=0V, f=1.0MHz$		2.0	pF
Reverse Recovery time	t_{rr}	$I_F=I_R=10mA, I_{rr}=0.1 \cdot I_R,$ $R_L=100\Omega$		4.0	ns

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




PACKAGE OUTLINE

Plastic surface mounted package



SOT-363		
Dim	Min	Max
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40
All Dimensions in mm		

SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
BAV756DW	SOT-363	3000 pcs / Tape & Reel