




## Features

- Two DTC143E transistors are built-in a package
- Built-in biasing resistors ( $R_1: 4.7\text{k}\Omega$ ,  $R_2: 4.7\text{k}\Omega$ )
- Transistor elements are independent, eliminating interference
- Mounting cost and area can be cut in half

## Mechanical Data

- Case: SOT-363
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



## Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
UMH15N	SOT-363	3000 pcs / Tape & Reel	H15

## Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
$V_{CBO}$	Collector-Base Voltage	50	V
$V_{CEO}$	Collector-Emitter Voltage	50	V
$V_{EBO}$	Emitter-Base Voltage	5	V
$V_{cc}$	Supply Voltage	50	V
$V_I$	Input Voltage	-10 to +30	V
$I_o$	Output Current	100	mA
$I_C(\text{Max})$	Collector Current	100	mA

## Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation *1	$P_D$	300	mW
Thermal Resistance, Junction to Ambient Air	$R_{\theta JA}$	417	°C/W
Operating Junction Temperature Range	$T_J$	-55 ~ +150	°C
Storage Temperature Range	$T_{STG}$	-55 ~ +150	°C

Note 1: Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint




## Electrical Characteristics (@ $T_A = 25^\circ C$ unless otherwise specified)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-base Cut-off Current	$I_{CBO}$	$V_{CB} = 50V, I_E = 0$	-	-	0.5	$\mu A$
Collector-emitter Cut-off Current	$I_{CEO}$	$V_{CE} = 30V, I_B = 0$	-	-	1	$\mu A$
Emitter-base Cut-off Current	$I_{EBO}$	$V_{EB} = 5V, I_C = 0$	-	-	1.8	mA
Input Voltage	$V_{I(OFF)}$	$V_{CC} = 5V, I_O = 100\mu A$	0.5	-	-	V
Input Voltage	$V_{I(ON)}$	$V_O = 0.3V, I_O = 20mA$	-	-	3	V
DC Current Gain	$h_{FE}$	$I_C = 10mA, V_{CE} = 5V$	20	-	-	-
Collector-Emitter saturation voltage	$V_{CE(sat)}$	$I_C/I_B = 10mA/0.5mA$	-	-	0.3	V
Input Resistor	$R_1$		3.29	4.7	6.11	$k\Omega$
Resistance ratio	$R_2/R_1$		0.8	1	1.2	-
Gain-Bandwidth Product	$f_T$	$V_{CE} = 10V, I_E = 5mA$ $f = 100MHz$	-	250	-	MHz




## Ratings and Characteristic Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




**Fig 1 Input Voltage vs Output Current**



**Fig 2 Output Current vs Input Voltage**




**Fig 3 DC Current Gain vs Output Current**



**Fig 4 Output Voltage vs Output Current**



### Package Outline Dimensions (Unit: mm)



SOT-363		
Dimension	Min.	Max.
A	2.00	2.20
B	1.15	1.35
C	0.85	1.05
D	0.15	0.35
E	0.25	0.40
G	0.60	0.70
H	0.02	0.10
J	0.05	0.15
K	2.20	2.40

### Mounting Pad Layout (Unit: mm)

SOT-363

