





Features

- Epitaxial planar die construction
- Complementary PNP type available(MMDT5401)

Mechanical Data

- Case: SOT-363
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



SOT-363

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMDT5551	SOT-363	3000 pcs / Tape & Reel	K4N

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V _{CBO}	180	V
Collector-Emitter Breakdown Voltage	V _{CEO}	160	V
Emitter-Base Breakdown Voltage	V _{EBO}	6	V
Collector Current (Continuous)	I _C	0.6	A
Collector Current (Peak)	I _{CM}	0.8	A

Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	0.2	W
Thermal Resistance Junction-to-Air	R _{θJA}	625	°C/W
Thermal Resistance Junction-to-Air *1	R _{θJA}	324	°C/W
Thermal Resistance Junction-to-Case *1	R _{θJC}	196	°C/W
Thermal Resistance Junction-to-Lead *1	R _{θJL}	214	°C/W
Junction Temperature Range	T _J	-55 ~ +150	°C
Storage Temperature Range	T _{STG}	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper



Electrical Characteristics (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	V _{(BR)CBO}	I _C = 100μA, I _E = 0	180	-	-	V
Collector-Emitter Breakdown Voltage	V _{(BR)CEO}	I _C = 1mA, I _B = 0	160	-	-	V
Emitter-Base Breakdown Voltage	V _{(BR)EBO}	I _E = 10μA, I _C = 0	6	-	-	V
Collector Cut-off Current	I _{CBO}	V _{CB} = 120V, I _E = 0	-	-	50	nA
Emitter Cut-off Current	I _{EBO}	V _{EB} = 4V, I _C = 0	-	-	50	nA
DC Current Gain	h _{FE}	V _{CE} = 5V, I _C = 1mA	80	-	-	-
		V _{CE} = 5V, I _C = 10mA	100	-	300	-
		V _{CE} = 5V, I _C = 50mA	30	-	-	-
Collector-emitter Saturation Voltage	V _{CE(sat)}	I _C = 10mA, I _B = 1mA	-	-	0.15	V
		I _C = 50mA, I _B = 5mA	-	-	0.2	V
Base-emitter Saturation Voltage	V _{BE(sat)}	I _C = 10mA, I _B = 1mA	-	-	1	V
		I _C = 50mA, I _B = 5mA	-	-	1	V
Collector-base Output Capacitance	C _{cbo}	V _{CB} = 10V, f = 1MHz, I _E = 0	-	-	6	pF
Current-Gain— Bandwidth Product	f _T	I _C = 10mA, V _{CE} = 10V f = 100MHz	100	-	300	MHz

Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1 h_{FE} vs. I_C




Fig 2 $V_{CE(sat)}$ vs. I_C




Fig 3 $V_{BE(sat)}$ vs. I_C





Fig 4 $V_{BE(ON)}$ vs. I_C




Package Outline Dimensions (Unit: mm)



Mounting Pad Layout (Unit: mm)

SOT-363



Package	Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
SOT-363	3000pcs	7inch	45,000pcs	203×203×195	180,000pcs	438×438×220