





### Features

- Epitaxial planar die construction
- Complimentary to BC807
- High collector current
- High current gain
- Low collector-emitter saturation voltage



### Mechanical Data

- Case: SOT-23
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



**SOT-23**

### Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BC817-16	SOT-23	3000 pcs / Tape & Reel	6A
BC817-25	SOT-23	3000 pcs / Tape & Reel	6B
BC817-40	SOT-23	3000 pcs / Tape & Reel	6C

### Maximum Ratings (@ T<sub>A</sub> = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Breakdown Voltage	V <sub>CBO</sub>	50	V
Collector-Emitter Breakdown Voltage	V <sub>CEO</sub>	45	V
Emitter-Base Breakdown Voltage	V <sub>EBO</sub>	5	V
Continuous Collector Current	I <sub>C</sub>	0.5	A
Peak Collector Current	I <sub>CM</sub>	1	A

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation	P <sub>D</sub>	300	mW
Thermal Resistance Junction-to-Air <sup>*1</sup>	R <sub>θJA</sub>	398	°C/W
Thermal Resistance Junction-to-Case <sup>*1</sup>	R <sub>θJC</sub>	230	°C/W
Thermal Resistance Junction-to-Lead <sup>*1</sup>	R <sub>θJL</sub>	202	°C/W
Operating junction Temperature	T <sub>J</sub>	-55 ~ +150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 ~ +150	°C

Note 1: The data tested by surface mounted on a 15mm \* 15mm \* 1mm FR4-epoxy P.C.B



### Electrical Characteristics (@ T<sub>A</sub> = 25°C unless otherwise specified)

Parameter		Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage		V <sub>(BR)CBO</sub>	I <sub>C</sub> = 100μA, I <sub>E</sub> = 0	50	-	-	V
Collector-Emitter Breakdown Voltage		V <sub>(BR)CEO</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> = 0	45	-	-	V
Emitter-Base Breakdown Voltage		V <sub>(BR)EBO</sub>	I <sub>E</sub> = 100μA, I <sub>C</sub> = 0	5	-	-	V
Collector Cut-off Current		I <sub>CBO</sub>	V <sub>CB</sub> = 25V, I <sub>E</sub> = 0	-	-	100	nA
Emitter Cut-off Current		I <sub>EBO</sub>	V <sub>EB</sub> = 4V, I <sub>C</sub> = 0	-	-	100	nA
DC Current Gain	BC817-16	h <sub>FE</sub>		100	213	250	-
	BC817-25			160	333	400	-
	BC817-40			250	383	600	-
	BC817-16		V <sub>CE</sub> = 1V, I <sub>C</sub> = 300mA	60	-	-	-
	BC817-25			100	-	-	-
	BC817-40			170	-	-	-
	BC817-40			V <sub>CE</sub> = 1V, I <sub>C</sub> = 500mA	40	-	-
Collector-emitter Saturation Voltage		V <sub>CE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	-	-	0.7	V
Base-emitter Saturation Voltage		V <sub>BE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	-	-	1.2	V
Transition Frequency		f <sub>T</sub>	I <sub>C</sub> = 50mA, V <sub>CE</sub> = 5V	-	170	-	MHz
Collector Output Capacitance		C <sub>OBO</sub>	V <sub>CB</sub> = 10V, I <sub>E</sub> = 0, f = 1MHz	-	6	-	pF



### Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




Fig 1  $h_{FE}$  vs.  $I_C$  (BC817-16)




Fig 2  $h_{FE}$  vs.  $I_C$  (BC817-25)




Fig 3  $h_{FE}$  vs.  $I_C$  (BC817-40)




Fig 4  $V_{BE(ON)}$  vs.  $I_C$




Fig 2  $V_{CE(sat)}$  vs.  $I_C$





Fig 3  $V_{BE(sat)}$  vs.  $I_C$




**Package Outline Dimensions** (Unit: mm)



SOT-23		
Dimension	Min.	Max.
A	2.70	3.10
B	1.10	1.50
C	0.9	1.1
D	0.3	0.5
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.05	0.15
K	2.20	2.60

**Package Outline Dimensions** (Unit: mm)

**SOT-23**



Package	Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
SOT-23	3000pcs	7inch	45,000pcs	203×203×195	180,000pcs	438×438×220