




1. EMITTER
2. COLLECTOR
3. BASE

### Features

- ✧ Complementary to KTA1273

### MAXIMUM RATINGS (T<sub>A</sub>=25°C unless otherwise noted)

Symbol	Parameter	Value	Units
V <sub>CB0</sub>	Collector-Base Voltage	30	V
V <sub>CEO</sub>	Collector-Emitter Voltage	30	V
V <sub>EBO</sub>	Emitter-Base Voltage	5	V
I <sub>C</sub>	Collector Current -Continuous	2	A
P <sub>C</sub>	Collector Power Dissipation	1	W
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>stg</sub>	Storage Temperature	-55-150	°C



Dimensions in inches and (millimeters)

### ELECTRICAL CHARACTERISTICS (T<sub>amb</sub>=25°C unless otherwise specified)







Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	V(BR) <sub>CB0</sub>	I <sub>C</sub> = 1mA, I <sub>E</sub> =0	30			V
Collector-emitter breakdown voltage	V(BR) <sub>CEO</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> =0	30			V
Emitter-base breakdown voltage	V(BR) <sub>EBO</sub>	I <sub>E</sub> = 1mA, I <sub>C</sub> =0	5			V
Collector cut-off current	I <sub>CB0</sub>	V <sub>CB</sub> = 30V, I <sub>E</sub> =0			0.1	μA
Emitter cut-off current	I <sub>EBO</sub>	V <sub>EB</sub> = 5V, I <sub>C</sub> =0			0.1	μA
DC current gain	h <sub>FE</sub>	V <sub>CE</sub> = 2 V, I <sub>C</sub> = 500 mA	100		320	
Collector-emitter saturation voltage	V <sub>CE (sat)</sub>	I <sub>C</sub> = 1.5A, I <sub>B</sub> = 30 mA			2.0	V
Base-emitter voltage	V <sub>BE</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> = 500mA			1.0	V
Transition frequency	f <sub>T</sub>	V <sub>CE</sub> = 2 V, I <sub>C</sub> = 500mA		120		MHz
Collector Output Capacitance	C <sub>ob</sub>	V <sub>CB</sub> =10V, I <sub>E</sub> =0, f=1MHz		13		pF

### CLASSIFICATION OF h<sub>FE</sub>

Rank	O	Y
Range	100-200	160-320



### Ratings and Characteristics Curve (TA=25°C unless otherwise noted)



Package	Packing	Quantity	Box	Box Size(mm)	Carton	Carton Size(mm)
TO-92L	Bulk	500pcs/Bag	5000pcs	245×170×100	50,000pcs	525×375×270
TO-92L	Tape	2000pcs/Tap	2000pcs	333×203×42	20,000pcs	493×400×264