





### Features

- Epitaxial die construction
- Complementary PNP type available (MMBT2907AM)
- Ultra-small surface mount package



### Mechanical Data

- Case: SOT-723
- Molding compound: UL flammability classification rating 94V-0
- Terminals: Tin-plated; solderability per MIL-STD-202, Method 208



**SOT-723**

### Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
MMBT2222AM	SOT-723	10000 pcs / Tape & Reel	1P

### Maximum Ratings (@ T<sub>A</sub> = 25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V <sub>CBO</sub>	75	V
Collector-Emitter Voltage	V <sub>CEO</sub>	40	V
Emitter-Base Voltage	V <sub>EBO</sub>	6	V
Collector Current (Continuous)	I <sub>C</sub>	600	mA
Collector Current - Peak pulse width ≤ 40μs, δ = 0.35	I <sub>CM</sub>	1.5	A
Continuous Base Current	I <sub>B</sub>	0.15	A
Peak Base Current	I <sub>BM</sub>	0.2	A

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation <sup>*1</sup>	P <sub>D</sub>	0.15	W
Thermal Resistance Junction-to-Air <sup>*1</sup>	R <sub>θJA</sub>	833	°C/W
Thermal Resistance Junction-to-Air <sup>*2</sup>	R <sub>θJA</sub>	190	°C/W
Thermal Resistance Junction-to-Case <sup>*2</sup>	R <sub>θJC</sub>	110	°C/W
Thermal Resistance Junction-to-Lead <sup>*2</sup>	R <sub>θJL</sub>	100	°C/W
Ambient Temperature	T <sub>A</sub>	-55 ~ +150	°C
Operating Junction Temperature	T <sub>J</sub>	-55 ~ +150	°C
Storage Temperature Range	T <sub>STG</sub>	-55 ~ +150	°C



### Electrical Characteristics (@ T<sub>A</sub> = 25°C unless otherwise specified)


Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub>	I <sub>C</sub> = 10μA, I <sub>E</sub> = 0	75	-	-	V
Collector-Emitter Breakdown Voltage	V <sub>(BR)CEO</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> = 0	40	-	-	V
Emitter-Base Breakdown Voltage	V <sub>(BR)EBO</sub>	I <sub>E</sub> = 10μA, I <sub>C</sub> = 0	6	-	-	V
Collector Cut-off Current	I <sub>CBO</sub>	V <sub>CB</sub> = 60V, I <sub>E</sub> = 0	-	-	10	nA
Collector Cut-off Current	I <sub>CEX</sub>	V <sub>CE</sub> = 60V, V <sub>BE</sub> = 3V	-	-	10	nA
Emitter Cut-off Current	I <sub>EBO</sub>	V <sub>EB</sub> = 3V, I <sub>C</sub> = 0	-	-	10	nA
DC Current Gain	h <sub>FE</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 0.1mA	35	-	-	-
		V <sub>CE</sub> = 10V, I <sub>C</sub> = 1mA	50	-	-	-
		V <sub>CE</sub> = 10V, I <sub>C</sub> = 10mA	75	-	-	-
		V <sub>CE</sub> = 10V, I <sub>C</sub> = 150mA	100	-	300	-
		V <sub>CE</sub> = 10V, I <sub>C</sub> = 500mA	40	-	-	-
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	-	-	1	V
		I <sub>C</sub> = 150mA, I <sub>B</sub> = 15mA	-	-	0.3	V
Base-Emitter Saturation Voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA	-	-	2	V
		I <sub>C</sub> = 150mA, I <sub>B</sub> = 15mA	-	0.6	1.2	V
Base-Emitter Voltage	V <sub>BE(on)</sub>	I <sub>C</sub> = 200mA, V <sub>CE</sub> = 10V	-	-	1	V
Transition Frequency	f <sub>T</sub>	V <sub>CE</sub> = 20V, I <sub>C</sub> = 20mA f = 100MHz	300	-	-	MHz
Output Capacitance	C <sub>OBO</sub>	V <sub>CB</sub> = 10V, I <sub>E</sub> = 0 f = 1MHz	-	-	8	pF
Noise Figure	N <sub>F</sub>	V <sub>CE</sub> = 10V, I <sub>C</sub> = 100μA R <sub>S</sub> = 1.0KΩ, f = 1.0kHz	-	-	4.0	dB
Delay Time	t <sub>d</sub>	V <sub>CC</sub> = 30V, I <sub>C</sub> = 150mA	-	-	10	ns
Rise Time	t <sub>r</sub>	V <sub>BE(OFF)</sub> = -0.5V, I <sub>B1</sub> = 15mA	-	-	25	ns
Storage Time	t <sub>s</sub>	V <sub>CC</sub> = 30V, I <sub>C</sub> = 150mA	-	-	225	ns
Fall Time	t <sub>f</sub>	I <sub>B1</sub> = -I <sub>B2</sub> = 15mA	-	-	60	ns

Notes:


- FR-5 = 1.0 \* 0.75 \* 0.062 in
- The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper




### Ratings and Characteristics Curves (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)




**Fig 1**  $h_{FE}$  vs.  $I_C$




**Fig 2**  $V_{CE(sat)}$  vs.  $I_C$




**Fig 3**  $V_{BE(sat)}$  vs.  $I_C$




**Fig 4**  $V_{BE(on)}$  vs.  $I_C$



**Fig 5**  $I_C$  vs.  $V_{CE}$




**Fig 6**  $P_D$  vs.  $T_A$



**Fig 7**  $C_J$  vs.  $V_R$




**Package Outline Dimensions** (Unit: mm)



SOT-723		
Dimension	Min.	Max.
A	1.10	1.30
B	0.70	0.90
C	0.40	0.54
D	0.22	0.42
E	0.10	0.30
F	0.12	0.32
G	0.70	0.90
J	0.08	0.15
K	1.10	1.30

**Mounting PAD Layout** (Unit: mm)

**SOT-723**



Package	Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
SOT -723	8000pcs	7inch	120,000pcs	203×203×195	480,000pcs	438×438×220