


FEATURES

- Epitaxial planar die construction.
- Ultra-small surface mount package.

APPLICATIONS

- Use as a medium power amplifier.



SOT-23		
Dim	Min	Max
A	2.70	3.10
B	1.10	1.50
C	1.0 Typical	
D	0.4 Typical	
E	0.35	0.48
G	1.80	2.00
H	0.02	0.1
J	0.1 Typical	
K	2.20	2.60
All Dimensions in mm		

ORDERING INFORMATION

Type No.	Marking	Package Code
MMBT2369A	1JA	SOT-23

MAXIMUM RATING @ Ta=25°C unless otherwise specified





Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	40	V
V_{CEO}	Collector-Emitter Voltage	15	V
V_{EBO}	Emitter-Base Voltage	4.5	V
I_C	Collector Current -Continuous	200	mA
P_C	Collector Dissipation	300	mW
$R_{\theta JA}$	Thermal resistance, junction to ambient	417	°C/W
T_j, T_{stg}	Junction and Storage Temperature	-55 to +150	°C



ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=10\mu A, I_E=0$	40			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C=10mA, I_B=0$	15			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=10\mu A, I_C=0$	4.5			V
Collector cut-off current	I_{CBO}	$V_{CB}=20V, I_E=0$			0.4	μA
Collector cut-off current	I_{CES}	$V_{CE}=20V, V_{BE}=0$			0.4	μA
DC current gain	h_{FE}	$V_{CE}=1.0V, I_C=10mA$	40		120	
		$V_{CE}=0.35V, I_C=10mA$	40			
		$V_{CE}=0.4V, I_C=30mA$	30			
		$V_{CE}=1.0V, I_C=100mA$	20			
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=10mA, I_B=1.0mA$ $I_C=30mA, I_B=3.0mA$ $I_C=100mA, I_B=10mA$			0.2 0.25 0.5	V
Base-emitter saturation voltage	$V_{BE(sat)}$	$I_C=10mA, I_B=1.0mA$ $I_C=30mA, I_B=3.0mA$ $I_C=100mA, I_B=10mA$	0.7		0.85 1.15 1.6	V
Output capacitance	C_{obo}	$V_{CB}=5V, I_E=0, f=1.0MHz$			4.0	pF
Storage time	t_S	$I_{B1}=I_{B2}=I_C=10mA$		5.0	13	ns
Turn-on time	t_{on}	$V_{CC}=3V, I_C=10mA,$ $I_{B1}=3mA$		8.0	12	ns
Turn-off time	t_{off}	$V_{CC}=3V, I_C=10mA,$ $I_{B1}=3mA, I_{B2}=1.5mA$		10	18	ns

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified



Package	Reel	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)
SOT-23	3000pcs	7inch	45,000pcs	203×203×195	180,000pcs	438×438×220