




### Features

- High collector current
- Complement to S9012L
- Excellent  $h_{FE}$  linearity



DFN1006-3

### Mechanical Data

- Case: DFN1006-3
- Molding compound: UL flammability classification rating 94V-0
- Terminal s: Tin-plated; solderability per MIL-STD-202, Method 208

### Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
S9013L	DFN1006-3	10000pcs / Tape & Reel	J3

### Maximum Ratings (@ $T_A = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	40	V
Collector-Emitter Breakdown Voltage	$V_{CEO}$	25	V
Emitter-Base Breakdown Voltage	$V_{EBO}$	5	V
Collector Current (Continuous)	$I_C$	500	mA

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation <sup>*1</sup>	$P_D$	250	mW
Junction Temperature	$T_J$	150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

Note 1: Device mounted on FR-4 PCB with minimum recommended pad layout



**Electrical Characteristics** (@  $T_A = 25^\circ\text{C}$  unless otherwise specified)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu\text{A}, I_E = 0$	40	-	-	V
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 0.1\text{mA}, I_B = 0$	25	-	-	V
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 100\mu\text{A}, I_C = 0$	5	-	-	V
Collector Cut-off Current	$I_{CBO}$	$V_{CB} = 40\text{V}, I_E = 0$	-	-	0.1	$\mu\text{A}$
Collector Cut-off Current	$I_{CEO}$	$V_{CE} = 20\text{V}, I_B = 0$	-	-	0.1	$\mu\text{A}$
Emitter Cut-off Current	$I_{EBO}$	$V_{EB} = 5\text{V}, I_C = 0$	-	-	0.1	$\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE} = 1\text{V}, I_C = 50\text{mA}$	120	-	400	-
		$V_{CE} = 1\text{V}, I_C = 500\text{mA}$	40	-	-	-
Collector-emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 0.5\text{A}, I_B = 0.05\text{A}$	-	-	0.6	V
Base-emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = 0.5\text{A}, I_B = 0.05\text{A}$	-	-	1.2	V
Current-Gain—Bandwidth Product	$f_T$	$I_C = 0.02\text{A}, V_{CE} = 6\text{V}$ $f = 30\text{MHz}$	150	-	-	MHz

**Classification Of  $h_{FE}$**

Rank	L	H	J
Range	120-200	200-350	300-400



**Ratings and Characteristic Curves** (@  $T_A = 25^\circ\text{C}$  unless otherwise specified)




Figure 1. Static Characteristic




Figure 2. DC current Gain




Figure 3. Base-Emitter Saturation Voltage  
Collector-Emitter Saturation Voltage





Figure 4. Current Gain Bandwidth Product



### Package Outline Dimensions (Unit: mm)



DFN1006-3			
Dimension	Min.	Typ.	Max.
A	0.95	1.00	1.075
B	0.47	0.50	0.53
C	0.55	0.60	0.675
D	0.45	0.50	0.55
E/J	0.20	0.25	0.30
F	-	0.40	-
G	-	0.35	-
H	0	0.03	0.05
I	0.10	0.15	0.20

### Package Outline Dimensions (Unit: mm)

#### DFN1006-3

